

Percent Oxygen Analyzer

Model 3020P

Teledyne's Model 3020P Percent Oxygen Analyzer is a versatile microprocessor-based instrument for detecting oxygen at the percent (%) level in a variety of gases. This instrument serves as the explosion-proof, bulkhead-mount version of the 3000P, and is designed to make the task of percent oxygen analysis easier, faster and more precise than ever before. Simple menu choices, externally accessible switches and dual LCD and LED displays make set-up and operation clear and quick.

Three User-Configurable Analysis Ranges

Three user-configurable ranges are standard, with an excellent linearity precluding the need to recalibrate when changing ranges. Two fully programmable concentration alarms provide the versatility to satisfy nearly any requirement. All features offer a sophistication that assures the 3020P will provide years of service.

Convenient Outputs For Data

Two standard 0-1 VDC outputs provide concentration and range identification. A bi-directional RS-232 serial interface is incorporated to relay information to a host computer for remote monitoring of critical functions.

Operator Interface

All controls and displays on the standard 3020P are accessible from the front of the instruments. The instrument has two simple operator controls. A digital meter, an alphanumeric display, and a sample flowmeter give the operator constant feedback from the instrument.

3020P ADVANTAGES

- Linearity of analysis across three user-selectable ranges
- AutoRanging capabilities
- Digital interface allows monitoring from a remote station
- Extended-life, maintenance-free sensor
- Comprehensive self testing function

STANDARD FEATURES

- An explosion proof NEMA 4/7 rated enclosure
- A 2-line alphanumeric display screen, driven by microprocessor electronics continuously prompting and informing the operator
- High resolution, accurate readings of oxygen content from low percent levels through 100%.
- Advanced Micro-Fuel Cell designed for percent analysis, with a six month warranty and an expected life of eight months
- Versatile analysis over a wide range of applications
- Microprocessor based electronics: 8-bit CMOS microprocessor with 32kB RAM and 128kB ROM



- Three user-definable output ranges (from 0-1% through 0-100%) assuring a perfect match for the user's process and equipment
- Air-calibration range for convenient spanning at 20.9%
- Auto-Ranging automatically selects the proper preset range for a given measurement. Manual override allows the user to lock onto a specific range of interest.
- Two adjustable concentration alarms and a system failure alarm
- Extensive self-diagnostic testing at start-up and on demand with continuous power-supply monitoring
- Two way RS-232 serial digital port for use with a computer or other digital communication device
- Two analog outputs measurement and range identification

APPLICATIONS

- *Monitoring inert gas blanketing*
- *Air separation and liquefaction*
- *Chemical reaction monitoring*
- *Semiconductor manufacturing*
- *Petrochemical process control*
- *Quality assurance*
- *Gas analysis certification*

TELEDYNE ANALYTICAL INSTRUMENTS

SENSORS ○ ANALYZERS ○ SYSTEMS ○ SCIENTIFIC SOLUTIONS

Specifications

Ranges: 3 customer programmable ranges
(minimum 0-1%) with AutoRanging

Calibration Range: 0-25%

Accuracy: +/- 2% of FS at a constant temperature
+/- 5% of FS over operating temperature
range (once temperature equilibrium has
been reached)

Sensitivity: 0.5% of FS

Response: (B-1) 90% of FS at 77°F (25°C) in less than
10 seconds

Operating Temperature: 32°F to 122°F (0°C to 50°C)

Signal Output: Analytical measurement - 0-1VDC

Range ID Output: 0-1VDC

Analysis Display: 5 digit red LED, 3/5" high numerals

Menu Display: 20 character, 2 line LCD

Data Lines: Bi-directional RS-232C serial interface,
baud rate 2400 - remote monitoring of all
critical functions

Alarm: One system failure alarm contact to detect
power, calibration, zero and sensor failure.
Two fully programmable concentration alarm set
points and corresponding form C 3 amp contacts.

Power Requirements: 115 / 230VAC, 50-60Hz

Oxygen Sensor: Teledyne Micro-Fuel cell, Class B-1
Optional: A3, A5, B-3, C-3

Wetted Parts: 316 stainless steel, nylon cell block

Sample Connections: 1/4" fittings

Area Classifications: Explosion proof enclosure is
U/L and CSA listed for Class I,
Division 1, Group B, C, D
service NEMA 4/7 rated

Mounting: Bulkhead mounting

Dimensions: 25.63" H x 15.25" W x 11" D

OPTIONS

- **C** Integrally mounted cal/zero valves
- **M** Isolated 4-20mADC signal and range ID output
- **V** Plumbed for vacuum service
- **F** Flame arrestors for Class I, Div 1, Group C/D
service
- **G** Flame arrestors for Class I, Div 1, Group C/D
service with cal valves
- **H** Flame arrestors for Group B (hydrogen) service
- **I** Flame arrestors for hydrogen service with
cal valves
- **S** Stainless steel cell holder

If you would like to meet with a member of the Teledyne team to discuss the Model 3020P or arrange a demonstration, please don't hesitate to contact your local representative.

TELEDYNE ANALYTICAL INSTRUMENTS

A Teledyne Technologies Company

16830 Chestnut Street
City of Industry, California 91748, USA

TEL: 626-934-1500 FAX: 626-934-1651

TOLL FREE: 888-789-8168

Visit Our Web Site at:
www.teledyne-ai.com

© 1997 Teledyne Analytical Instruments, A Teledyne Technologies Company.
All rights reserved. Printed in the USA. 3/97LD

Regional Offices

Tokyo, Japan81-33-239-9090

Rio de Janeiro, Brazil.....55-21-531-1722

Warranty

Instrument is warranted for 1 year against defects in material or workmanship

NOTE: Specifications and features will vary with application. The above are established and validated during design, but are not to be construed as test criteria for every product. All specifications and features are subject to change without notice.

