

# LaserGas™ Q SO<sub>2</sub> (QCL edition)



**NEO Monitors LaserGas™ Q SO<sub>2</sub> (QCL edition)** is using Tuneable Laser Absorption Spectroscopy (TLAS) i.e a non-contact optical measurement method employing solid-state laser sources. The sensor remains unaffected by contaminants corrosives and does not require regular maintenance. The absence of extractive conditioning systems further improves availability of the measurements and eliminates errors related to sample handling. The monitor is mounted directly onto flanges, which include purge gas connections and a tilting mechanism for easy alignment. Continuous purge flow prevents dust and other contamination from settling on the optical windows. Once power and data lines are connected, measurements are performed in real-time.

## Features

- Fast response time
- No gas sampling: In-situ measurement
- Limited interference from background gases
- Line measurement, integral concentration over the full stack diameter
- Suitable for harsh environment
- No zero drift
- Stable calibration

## Applications

LaserGas™ Q SO<sub>2</sub> (QCL edition) is designed for reliable and fast measurement of sulphur dioxide in continuous emission monitoring and process control.

## Customer benefits

- In-situ monitoring
- Highly reliable real time analyzer
- Low maintenance cost
- Reduce emission to the environment
- Easy to install and operate
- Reduce daily operation costs
- Optimize process
- Well proven measurement technique

# LaserGas™ Q SO<sub>2</sub> (QCL edition)

## Technical Data

<p><b>Specifications</b></p> <p>Optical path length: Typically 0.5 - 6 m            Response time: Typically 10 - 20 sec (other response time request)            Accuracy: Application dependent            Repeatability: 1% of range (gas &amp; application specific)</p> <p>Range SO<sub>2</sub>: 0 - 2000 ppm (other ranges on request)</p> <p>Detection limit: 1 ppm            Temperature: 200 °C - 400 °C (other temperatures on request)</p> <p>Pressure: 0.7 - 1.5 bar abs            Windows material: CaF<sub>2</sub></p> <p><b>Environmental conditions</b></p> <p>Operating temperature: -20 °C to +55 °C            Storage temperature: -20 °C to +55 °C            Protection classification: IP66</p> <p><b>Inputs / Outputs</b></p> <p>Analog output (3): 4 - 20 mA current loop (concentration, transmission)            Digital output: RS - 232 format, Optional 10 or 10/100 Base T Ethernet, Optional fiber optic (ASCII - format)            Relay output (3): High gas-, Maintenance-, Warning - and Fault relays (normally closed-circuit relays)            Analog input (2): 4 - 20 mA process temperature and pressure reading</p>	<p><b>Ratings</b></p> <p>Input power supply unit: 100 – 240 VAC, 50/60 Hz            Output power supply unit: 24 VDC, 900 – 1000 mA            Input transmitter unit: 18 – 36 VDC, max. 20W            4 – 20 mA output: 500 Ohm max. isolated            Relay output: 1 A at 30 V DC/AC</p> <p><b>Installation and Operation</b></p> <p>Flange dimension alignment: DN50/PN10 or ANSI 2"/150lbs (other dimensions on request)            Alignment tolerances: Flanges parallel within 1.5°            Purge flow: Dry and oil-free pressurized air or nitrogen 10 - 50 l/min (application dependent)            Purging of laser: Clean dry air, ≈ 15 l/min <b>(Mandatory)</b>            Purging of windows: Dry and oil-free pressurized air or gas, or by fan</p> <p><b>Maintenance</b></p> <p>Visual inspection: Recommended every 6 – 12 months            Calibration: Check recommended every 12 months</p>	<p><b>Safety</b></p> <p>Laser class: Class 1 according to IEC 60825-1            CE: Certified            EMC: Conformant with directive 2014/30/EU            ATEX: PENDING            CSA: PENDING</p> <p><b>Dimension and weight</b></p> <p>Transmitter unit: 340 x 270 x 170 mm, 6.9 kg            Receiver unit: 260 x 270 x 170 mm, 5.5 kg            Power supply unit: 180 x 85 x 70 mm, 1.6 kg</p>
---	---	---

\*NEO Monitors reserve the right to change specifications without prior notice

Your local distributor:

**Technopomiar**

Everything You need to measure



Technopomiar 105, Graniczna Str. PL54530 Wrocław Poland



neomonitors

NEO Monitors as • A subsidiary of Norsk Elektro Optikk  
 Prost Stabels vei 22 • N-2019 Skedsmokorset, Norway • Phone +47 67 97 47 00 • [www.neomonitors.com](http://www.neomonitors.com)